



DSCAN S600

Efficient
Convenient
Durable



Bring speed a power to you checkout process



What's Special?

Made for high volume environments, the DSCAN S600 comes with a capacity of scanning speed 1500 scan lines per second & 75 scan lines per second and 20 lines Omnidirectional fields.



Specifications

Light Source	Visible Laser Diode 650nm
Scan Pattern	20 lines Omnidirectional: 5 fields of 4 parallel lines
Scan Speed	1500 scan lines per second & 75 scan lines per second
Print Contrast	30% - UPC/EAN 100%
Minimum Resolution	5mil - PCS90%
Depth of Field	0-200mm for 0.33mm UPC/EAN 100%
Decode Capability	UPC/EAN/JAN, UPC/EAN with supplementary, JAN 8& JAN 13, ISBN/ISSN, EAN, Code 39, Code 39 with full ASCII, Code 93, Code 128, Codabar (NM7), Trioptic Code 39, MSI/Plessey, Interleaved 2 of 5 (ITF), Addendum 2 of 5, IATA Code, China Post Code, Code 32, Industrial 2 of 5, Standard 2 of 5, Discrete 2 of 5, Matrix 2 of 5, Code 11, UPC/EAN RSS, RSS variants.
Host System Interfaces	USB, RS232 and PS2 optional
Visual Indicators	Two color LED (blue & red)
Beeper Operation	Programmable tone & Volume
Mechanical Parameter	
Size	105mm x 100mm x 156mm
Weight	300 g
Material	ABS+PC
Electrical Parameter	
Voltage	5 Volts
Power	1.0 watt
Static Current	200mA
Environmental Parameter	
Operating Temperature	0°C to 45°C
Storage Temperature	-20°C to 60°C
Humidity	5% to 85% relative humidity, non-condensing
Light Levels	Daylight, 5000Lux
Shock	Designed to withstand 1.5M drops